

CAT 6 UTP KEYSTONE JACK JKA09-UC6



[PRODUCT DESCRIPTION]

This series keystone jacks work together with high speed cables, cords and panels to provide performance beyond proposed Category 6 standards, a new feature of this series jack is a universal colored wiring label that eliminates the need for separate codes for T568A/B wiring scheme.

[TECHNICAL SPECIFICATION]

- Available in Cat6, T568A/B wiring, meet or exceed TIA/EIA Cat6 requirements
- Housing : high temperature thermoplastic
- Compact jack design, 8 positions and 8 conductors
- Contact : phosphor bronze , phosphor bronze with 6 to 50 μ "gold plate
- Accept 22-26 AWG solid with a insulation diameter of 0.4-0.6 mm
- Easy to be terminated, low attenuation loss and high return loss
- High reliability and superior performance
- Available in different colors

[CONSTRUCTION]

Description	Parameter
Contact resistance(max)	100m Ω
Insulation resistance (min)	500M Ω
Return loss (dB)	5.8dB
Next (dB)	4.7dB
Ps next(dB)	5.5dB

[ORDER INFORMATION]

Part number	Description	standard color	Inner box	Carton	Carton measurement	Carton weight
JKA09-UC6	Cat6 unshielded keystone jacks (180 degree)	White	25PCS	250PCS	L 53.5cm × W 31.3cm × H 23.4cm	3.80KG