

CAT 6 UTP PATCH PANEL PNA24-UC6



[PRODUCT DESCRIPTION]

The shielded patch panels are loaded with shielded keystonejacks, which are housed in a closure full shielding metal enclosure designed to meet highest industry requirement. A shielded version is also available to maximum protection from EMI/RFI interference. By utilizing fully shielded jacks and connecting hardware, you can reduce the effects of interference on the network data transmissions.

[TECHNICAL SPECIFICATION]

- Design to mount to any standard 19" rack or cabinet
- 24 -port Cat 6 non shielded Patch panel
- Space saving, high-density 1U
- Black Electrostatic Powder-Coated Steel: phosphor bronze with tinplating over nickel. Meet or exceed the requirement of SI /TIA/EIA568B.2
- Use keystone jacks and keystone inserts to configure your panel to accommodate a variety of schemes
- Sturdy Aluminum Plate around RJ 45 Jacks
- Phosphor bronze with 6-50 micro inches gold plated
- Available with T568 A. T568 B wiring pattern and meeting the requirement of Cat 6 standard
- Color Coded TIA/EIA 568A (international) and 568B (AT&T Standard) Wiring For Easy Installation
- Termination accepts 22,24 26 AWG (0.64,0.5 and 0.4) solid wires
- Metal sheet: Corrosion resistant steel
- Plastic: fire self -extinguish high impact plastic

[ORDER INFROMATION]

Part number	Description	standard	Inner	Carton	Carton	Carton
		color	box		measurement	weight
PNA24-UC6	24-port Cat6	Black	1PCS	10PCS	L 53.5cm× W	10.00KG
	unshielded patch				31.3cm × H	
	panels (jack style)				23.4cm	
	(JKA09-UC6)					
PNA24-KJ	Empty panel	Black	1PCS	10PCS	L 53.5cm× W	7.80KG
					31.3cm × H	
					23.4cm	