

## CAT6FTP 24-PORT PATCH PANEL PNS24-SC6-0.5



## [PRODUCT DESCRIPTION]

Cat6 patch panel adapt 110 style terminating, designed to satisfies or even exceeds current CAT6 standard; guarantees 350MHZ broadband transmission, long-term reliability and stability; suitable for connection between workspace and Equipment room.

## [TECHNICAL SPECIFICATION]

- Design to mount to any standard 19" rack or cabinet
- 24 -port Cat 5E shielded Patch panel
- Space saving, high-density 1U
- Black Electrostatic Powder-Coated Steel: phosphor bronze with tin plating over nickel. Meet or exceed the requirement of ANSI /TIA/EIA 568B.2
- Use keystone jacks and keystone inserts to configure your panel to accommodate a variety of schemes
- Sturdy Aluminum Plate around RJ 45 Jacks
- Phosphor bronze with 6-50 micro inches gold plated
- Available with T568 A. T568 B wiring pattern and meeting the requirement of Cat 6A standard
- Color Coded TIA/EIA 568A (international) and 568B (AT&T Standard) Wiring For Easy Installation
- Termination accepts 22,24 26 AWG (0.64,0.5 and 0.4) solid wires
- Metal sheet: Corrosion resistant steel
- Plastic: fire self -extinguish high impact plastic



## [ORDER INFROMATION]

Part number	Description		standard	Inner	Carton	Carton	Carton
			color	box		measurement	weight
PNS24-SC6-0.5	24-port	Cat5e	Black	1PCS	5PCS	L 53.5cm ×	8.60KG
	shielded	patch				W 31.3cm $ imes$	
	panels (IDC	C style)				H 23.4cm	