

SINGLE MODE SC FAST OPTICAL CONNECTOR FBS12-1



[PRODUCT DESCRIPTION]

SC fiber optic connector for quick follow 0.25mm/0.9mm/2.0mm/3.0mm / covered wire cable. Not only can easily end into the optical fiber into the panel box, and can directly access the ONU, dual-core dual-side skin splice cable, outdoor fiber optic cable burglary, a comprehensive coverage of various requirements of FTTX FTTH; another jumper can be produced at the construction site substantially increase efficiency

[TECHNICAL SPECIFICATION]

- Quick follow-connector insertion loss is less than 0.3 dB, is the smallest loss of similar products.
- Online tensile strength greater than 20N, the normal force in the customer wiring or non-accidental tension when not affect the use, and the maximum tensile strength greater than 50N.
- Products in non-consecutive points and the matching fluid, greatly reduce the home consumption, to improve life.
- Do not need routine maintenance in the water, into the dust pollution, the user can clean the joint surfaces, without engineers on-site ervice, greatly reducing the cost of post-use 5.
- Construction, visualization, and can find cutting issues, reduce the cutting tool wear caused by the loss of rework.

[ORDER INFROMATION]

Part number	Description	standard color	Inner box	Carton	Carton measurement	Carton weight
FBS12-1	single mode SC Fast optical connector		20PC			