




Bow-type drop Cable,single mode,simplex

PRODUCT FIGURE



FCS11-1-S Cable Structure

ORDER INFORMATION

Part number	Description	Standard Color
FCS11-1-S-LSZH	Bow-type drop Cable,single mode,simplex	Black

BOW-TYPE DROP CABLE,Single mode, GJXFH,simplex, PE sheath, Steel wire strength,black color.

DESCRIPTION

The optical fiber unit is positioned in the centre. Two parallel Fiber Reinforced Plastics (FRP) are placed at the two sides. Then, the cable is completed with a black or color LSZH sheath.

APPLICATION

- Special low-bend-sensitivity fiber provides high bandwidth and excellent communication transmission property
- Two paeallel FRP strength membersnsure good perfor crush resistance to protetmthe fiber
- Simple Structure, light weight and high practicability
- Novel flute desing. easily strip and splice simplify the installation and maintenance
- Low smoke, zero halogen and flam retardant sheath.

TECHNICAL PARAMETERS

Fiber Count	Cable Size (mm)	Cable Weight (kg/km)	Tensile Strength Long/Short Term (n)	Crush Resistance Long/Short Term (N/100mm)	Bending Radius Static/Dynamic (mm)
1	(2.0±0.1)×(3.0±0.1)	8	40/80	500/1000	15/30
2	(2.0±0.1)×(3.0±0.1)	8.5	40/80	500/1000	15/30