


**BOW-TYPE DROP CABLE,SINGLE MODE,DUPLX P/N:FCS11-2-F-LSZH S/N:F07-003**



Bow-type drop Cable,single mode,duplex

### PRODUCT FIGURE



FCS11-2-F Cable Structure

### ORDER INFORMATION

| Part number  | Description                            | Standard Color |
|--------------|--|----------------|
| FCS11-2-LSZH | Bow-type drop Cable,single mode,duplex | Black          |

BOW-TYPE DROP CABLE,Single mode, GJXFH,simplex, PE sheath, FRE strength,black color.

### DESCRIPTION

The optical fiber unit is positioned in the centre. Two parallel Fiber Reinforced Plastics (FRP) are placed at the two sides. Then, the cable is completed with a black or color LSZH sheath.

### APPLICATION

- Special low-bend-sensitivity fiber provides high bandwidth and excellent and excellent communication transmission property
- Two paeallel FRP strength membersnsure good perfor crush resistance to protetmthe fiber
- Simple Structure, light weight and high practicability
- Novel flute desing. easily strip and splice simplify the installation and maintenance
- Low smoke, zero halogen and flam retardant sheath.

### TECHNICAL PARAMETERS

| Fiber Count | Cable Size (mm)     | Cable Weight (kg/km) | Tensile Strength Long/Short Term (N) | Crush Resistance Long/Short Term (N/100mm) | Bending Radius Static/Dynamic (mm) |
|-------------|---------------------|----------------------|--------------------------------------|--|------------------------------------|
| 1           | (2.0±0.1)×(3.0±0.1) | 8                    | 40/80                                | 500/1000                                   | 15/30                              |
| 2           | (2.0±0.1)×(3.0±0.1) | 8.5                  | 40/80                                | 500/1000                                   | 15/30                              |