

**CAT 6 UTP 24-PORT PATCH PANEL P/N: CAA01-UC6-\*-\*# S/N: C02-004**

## DESCRIPTION

- Adopt LINKBASIC Cat6 stranded cable and Cat6 RJ45 modular plugs, the performance of LINKBASIC patch cable can meet or exceeds all requirements for Cat6 standard . Compatible with LINKBASIC Cat6 keystone jacks and Cat6 24 port patch panel, guarantees 350MHZ broadband transmission .

## FEATURES

- Unique design of Cat6 RJ45 modular plugs and line pair decrease cross talk and increase allowance.
- Excellent attenuation and crosstalk continuity
- Meet or exceed the requirement for UTP system
- 100% tension test
- Allow RJ45 plugs to provide high-density solution
- Available in different colors
- They are available in a variety of the length

## APPLICATION

- Communication outlet
- Concentration point
- Patch panel
- Equipment termination

## MECHANICAL CHARACTERISTIC;

- Durability: 1000 plugging
- Contact: phosphor bronze with 50μ" gold plating
- Nominal outer diameter: 5.6mm
- Minimum bending radius: 22.4mm

## PHYSICAL CHARACTERISTICS

- Conductor: 23 AWG bare copper
- Insulation material: PE
- Outer shield: AL Foil
- Structure: 4 twisted pair, Cross filler
- Jacket for RJ45 plug: PVC or LSZH
- Material for RJ45 plus: PC polycarbonate
- Flame test: CM or CMR

## ORDER INFORMATION

Part number	Description	Inner box	Carton measurement
CAA01-UC6-*-*#	Cat 6 UTP Patch Cable	1PC	L 53.5cm× W 31.3cm × H 23.4cm
CAA01-UC6-LSZH-*-*#	Cat 6 UTP Patch Cable	1PC	L 53.5cm× W 31.3cm × H 23.4cm
CAA01-UC6-CMR-*-*#	Cat 6 UTP Patch Cable	1PC	L 53.5cm× W 31.3cm × H 23.4cm

Use \* to specify the length : 1=1 meter , 2= 2 meters , 3=3 meters , 0.2=0.2 meters

Use # to specify the color : A = black B =blue C =red D= orange E=yellow F= gray G =green

PATCH CORD, CAT6, UTP, RJ45, molded boot, available in different length and color.



CAA01-UC6-\*-\*#

CAT 6 UTP PATCH CABLE (CAA01-UC6-\*-\*#)

## ELECTRICAL CHARACTERISTICS

Dielectric strength	1,000V RMS 60Hz/1min
Voltage Class(maximum)	150VAC
Rated current(maximum)	1.5A
Insulation resistance(minimum)	500megohm
Contact resistance(maximum)	10milliohm

## PRODUCT FIGURE

