




Bow-type drop Cable, Multi mode, simplex

### PRODUCT FIGURE



FCM11-1-S Cable Structure

### ORDER INFORMATION

Part number	Description	Standard Color
FCM11-1-S-LSZH	Bow-type drop Cable, Multi mode, simplex	Black

BOW-TYPE DROP CABLE, Multi mode, GJXF-H, simplex, PE sheath, Steel wire strength, black color.

### DESCRIPTION

The optical fiber unit is positioned in the centre. Two parallel Fiber Reinforced Plastics (FRP) are placed at the two sides. Then, the cable is completed with a black or color LSZH sheath.

### APPLICATION

- Special low-bend-sensitivity fiber provides high bandwidth and excellent communication transmission property
- Two parallel FRP strength members ensure good performance for crush resistance to protect the fiber
- Simple Structure, light weight and high practicability
- Novel flute design. easily strip and splice simplify the installation and maintenance
- Low smoke, zero halogen and flame retardant sheath.

### TECHNICAL PARAMETERS

Fiber Count	Cable Size (mm)	Cable Weight (kg/km)	Tensile Strength Long/Short Term (N)	Crush Resistance Long/Short Term (N/100mm)	Bending Radius Static/Dynamic (mm)
1	(2.0±0.1)×(3.0±0.1)	8	40/80	500/1000	15/30
2	(2.0±0.1)×(3.0±0.1)	8.5	40/80	500/1000	15/30