

DESCRIPTION

- Cat5E patch panel is equipped with 24port unshielded JKA08-UC5E keystone jacks and designed to meet or exceeds the requirement of CAT5E standard; guarantees 250MHZ broadband transmission, long-term reliability and stability; suitable for connection between workspace and Equipment room.


FEATURES

- Exquisite and compact appearance.
- Unique design of balance circuit board and line pair decrease cross talk and increase allowance.
- The IDC phosphor bronze wiring clip ensures 250 terminating.
- Latch design on terminating protective cap can prevent cable from over bending or falling off after termination, and prevent contact point from damage.
- Backward compatibility for Cat5
- 25 μ " gold plating contact allows 1500 matching recycles
- Sturdy and easy-install design reduces installation and operating costs.
- IDC terminating compatible with 110 or KRONE tools.
- Compatible with 19 inch rack, cabinet and wall mount.
- Number marking at front and back side of each port, enable quick identification.
- Cable management at back can effectively lead the cable to the termination.


APPLICATION

- Horizontal cabling or equipment termination in the device room
- Matching termination collected.

PRODUCT FIGURE



PATCH PANEL, CAT5E, UTP, 19inch, T568A/B, 24ports, 1U, keystone type. S/N:C06-008



CAT 5E UTP 24-port patch panel (180 degree, jack style, JKA09-UC5E)

ELECTRICAL CHARACTERISTICS

Dielectric strength	1,000V RMS 60Hz/1min
Rated current	Maximum 1.5A
Insulation resistance(minimum)	500megohm
Contact resistance(maximum)	100milliohm

SPECIFICATION

- Suitable for 24AWG cable
- IDC terminating interface
- Durability: 1500 times plugging
250 times terminating

PHYSICAL CHARACTERISTICS

- IDC interface
- IDC clip: phosphor bronze.
- Module style jack socket
- Contact: phosphor bronze with 25 μ " gold plating
- Empty panel: cold-rolled steel sheet frame, with electrostatic spray on the surface, color in black, back and bracket galvanized.




LINKBASIC

CAT 5E UTP SYSTEM PRODUCTS

CAT 5E UTP 24-PORT PATCH PANEL

P/N: PNA24-UC5E

PRODUCT FIGURE



INSTALLATION INSTRUCTIONS



The bracket of Cat5E patch panel.



Position the shielded keystone jack after crimping.



Insert the jack into mounting port properly

TRANSMISSION PERFORMANCE

Frequency (MHz)	Insertion loss (Db)	Next (Db)	PSNext (Db)	RL (Db)
1	0.02	86.3	58.1	87.0
4	0.03	75.8	48.5	76.3
8	0.04	70.2	43.2	70.4
10	0.03	68.6	42.0	68.8
16	0.2	65.0	38.2	64.5
20	0.09	63.2	36.4	62.7
25	0.08	61.4	34.8	60.8
31.25	0.05	59.7	32.9	58.6
62.5	0.07	54.4	27.2	52.3
100	0.09	50.7	23.7	47.3

ORDER INFORMATION

Part number	Description	standard color	Inner box	Carton	Carton measurement	Carton weight
PNA24-UC5E	24-port Cat5e unshielded patch panels (jack style) (JKA09-UC5E)	Black	1PC	10PCS	L 53.5cm× W 31.3cm × H 23.4cm	10.00KG



LINKBASIC

WWW.LINKBASIC.COM

CAT 5E UTP 24-PORT PATCH PANEL

Copper solution